

FCA-3200



- **Time Attendance:** support time attendance for employee and visitor via face-recognition.
- Mask Detection: support mask detection and reminder or forbidden for not wearing the mask
- Multi-interface: support wiegand, alarm in/out to work with 3rd access control for alarm linkage
- empeo certified product

Product Highlights

- **High Performance**: 50,000 face database with high accuracy and high speed for recognition
- Easy Installation: multiple installation, like wall-mounting, pole standing, or work with turnstile
- Superior recognition in any environment: working in different light environment, even low light scene
- **High Security**: RGB+IR liveness detection, effectively defending against various forms of attacks such as photos,3D paper models
- Multifunction: face recognition, Mifare card and password for authentication







Mifare Card



7-inch Touchscreen



Built-in



TCP/IP



IOMO

iomo







Specification

Model	FCA-3200
Parameter	
Touch Screen	Support
Screen Size	7inch
Dimension	211mm*112mm*22.5mm
Sensor	RBG + IR Dual 2MP
Resolution	1024*600
Screen Brightness	Support to adjust
IR Fill Light	Support
Face Database	50,000
WiFi	Support
Authentication	Card/Password/Face
Interface	
Tamper Interface	Support
Reset Interface	Support
Input Interface	Alarm input*2; Sensor input*1; Exit button*1
Output Interface	Alarm output*1; Sensor output*1
Data Transmission Interface	Wiegand 26/34(input/output selectable) ; USB Type A*1 ; USB Type C*1 ; RS485*1
Network Port	100M
Mic	Support
Card	
Card Type	Mifare card
Frequency	13.56 MHz
Other Parameter	
Power	DC 12V/2A
Working Temperature	-20°C~65°C
Protection Level	IP65
Installation	wall-mounting, turnstile, pole standing
Standard Accessory	Wall bracket, Power Supply

No.

Name





1	Visible light camera
2	Infrared camera
3	Infrared fill light
4	Display screen
5	Card tap area
6	Indicator light
7	USB port
8	External cable connection
9	3.5mm headphone jack
10	Tamper prevention button
11	Speaker

Description
Captures visible light images
Captures infrared images
Provides fill light for the infrared camera
7-inch multi-touch display screen
Users tap their cards here
Indicates the access result and power status
A Type C port for connection with USB drives
Used for connection to a power source
Connect external active speakers
Prevents disassembly after installation
Plays audio prompts